

COLOR OPTIONS



Dupont



Montana



White



Granite



Northwest

REQUESTING SAMPLES

Interested in receiving Xeripave samples, please e-mail us at info@xeripave.com or call **(800) 377-3877**.



Tip: For area with vehicular traffic we recommend using Xeribrix, which is available in Dupont and Montana.

SIZE SELECTION

Xeripave® SP Pavers (Square)

11.81 x 11.81 x 1.97in (300mm x 300mm x 50mm)

15.75 x 15.75 x 1.97in (400mm x 400mm x 50mm)

11.81 x 11.81 x 3.56in (300mm x 300mm x 90mm)

XeriBrix® Pavers (Rectangular)

4.5 x 9 x 2.38in (115mm x 230mm x 60mm)

XERIPAVE HEADQUARTERS

815 NE 172nd Ave
Vancouver, WA 98684

Toll Free: 1 (800) 377-3877

Local: (360) 694-0141

Fax: (360) 694-0281

Email: info@xeripave.com

WWW.XERIPAVE.COM



(800) 377-3877 | WWW.XERIPAVE.COM

WHAT IS XERIPAVE?

Xeripave Super Pervious (SP) Pavers are natural rock pavers made with an inert polymer binder. It has an unparalleled flow through rate of up to one gallon per second per square foot, or 90 inches per minute with an open basin drainage system.

HOW IS IT USED?

Xeripave pavers can be economically installed in any area in place of, or in conjunction with traditional paving materials such as asphalt, concrete or bricks. Due to Xeripave's unparalleled infiltration rate, only 12-18% of total surface coverage is needed for optimal drainage. Xeripave is truly super pervious with a void capacity exceeding 33 percent.



THE ONLY SUPER PERVIOUS PAVER WITH A FLOW RATE OF ONE GAL PER SECOND!

PATTERNS AND STYLES



SP Pavers Pavers



XeriBrix Pavers



SP Pavers Pavers & Concrete Pavers

APPLICATION:

Xeripave SP Pavers capture stormwater runoff allowing the water to flow through the surface, while leaving behind gross pollutants. SP Pavers are often found in applications such as:

- ✔ Tree surrounds
- ✔ Patios, Pathways, and Courtyards
- ✔ Trench and Strip Drains
- ✔ Parking Lots and Driveways (Xeribrix Recommended)
- ✔ Green Roofs
- ✔ Bioswales
- ✔ Dog Parks
- ✔ Water Harvesting Systems

Xeripave provides a great pedestrian surface that is ADA slip and skid resistant. Suitable for residential and commercial applications as well as low-impact traffic.



INSTALLATION DETAILS:

Rock sub-base must create large enough reservoir capacity to accommodate high inflow rate. Bedding layer is typically 1" thick at ASTM No.8 clean-crushed aggregates (1/2" No.16). Underplaying cross section varies, technical data and installation manual is available on our website at www.xeripave.com.



CLEANING:

Xeripave SP Pavers need to be cleaned periodically, but are easily maintained using a pressure washer, shop-vac or city sweeper. The frequency of maintenance is dependent on the contaminant profile of the area.